

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name**

**edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in:  
edding 800 (4521001)**

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture**

Refill ink

**Uses advised against**

No data available.

### 1.3 Details of the supplier of the safety data sheet

**Address**

edding International GmbH

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

**Information provided by / telephone**

+49 (0)4102 - 808-0

**Advice on Safety Data Sheet**

sdb\_info@umco.de

### 1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

### 2.2 Label elements

**Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)**

**Hazard pictograms**



GHS02



GHS07

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

1-methoxy-2-propanol

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

**Hazard statement(s)**

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

**Precautionary statement(s)**

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 Use only outdoors or in a well-ventilated area.  
P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.  
P405 Store locked up.  
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients**
**3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures**
**Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	<b>1-methoxy-2-propanol</b>		
	107-98-2 203-539-1 603-064-00-3 -	Flam. Liq. 3; H226 STOT SE 3; H336	>= 25.00 - < 50.00 wt%
2	<b>ethanol</b>		<b>pls. refer to footnote (1)</b>
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225 Eye Irrit. 2; H319	>= 25.00 - < 50.00 wt%
3	<b>Poly(oxy-1,2-ethanediyl), alpha-decyl-omega-hydroxy-, phosphate</b>		
	52019-36-0 - - -	Eye Dam. 1; H318 Skin Irrit. 2; H315	< 5.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

(1) Aberrant from/in addition to the classification set out in Annex VI, this substance is classified according to European Regulation (EC) No 1272/2008 (CLP), Article 4 (3), paragraph 2.

No	Note	Specific concentration limits	M-factor (acute)	M-factor (chronic)
2	-	Eye Irrit. 2; H319: C >= 50%	-	-

**3.3 Other information**

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

**SECTION 4: First aid measures**
**4.1 Description of first aid measures**
**General information**

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

**After inhalation**

Remove affected person from the immediate area. Ensure supply of fresh air.

**After skin contact**

Wash off immediately with soap and water. Do NOT use solvents or thinners.

**After eye contact**

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

**After ingestion**

Rinse out mouth and give plenty of water to drink. Call a doctor immediately. Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available.

## SECTION 5: Firefighting measures

**5.1 Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam; Extinguishing powder; Carbon dioxide; Water spray jet

**Unsuitable extinguishing media**

High power water jet

**5.2 Special hazards arising from the substance or mixture**

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

**5.3 Advice for firefighters**

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Suppress gases/vapours/mists with water spray jet. Wear protective clothing.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). Send in suitable containers for recovery or disposal.

**6.4 Reference to other sections**

No data available.

## SECTION 7: Handling and storage

**7.1 Precautions for safe handling**

**Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary).

**General protective and hygiene measures**

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

**Advice on protection against fire and explosion**

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

**7.2 Conditions for safe storage, including any incompatibilities**

**Technical measures and storage conditions**

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

**Requirements for storage rooms and vessels**

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

**Incompatible products**

Do not store together with: Acids; Alkalis; oxidizing agents

**7.3 Specific end use(s)**

No data available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

**Occupational exposure limit values**

No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
	2000/39/EC		
	1-Methoxypropanol-2		
	WEL short-term (15 min reference period)	568	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Skin resorption / sensibilisation	Skin	
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	1-Methoxypropan-2-ol		
	WEL short-term (15 min reference period)	560	mg/m <sup>3</sup> 150 ppm
	WEL long-term (8-hr TWA reference period)	375	mg/m <sup>3</sup> 100 ppm
	Comments	Sk	
2	ethanol	64-17-5	200-578-6
	<b>List of approved workplace exposure limits (WELs) / EH40</b>		
	Ethanol		
	WEL long-term (8-hr TWA reference period)	1920	mg/m <sup>3</sup> 1000 ppm

**8.2 Exposure controls**

**Appropriate engineering controls**

No data available.

**Personal protective equipment**

**Respiratory protection**

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

**Eye / face protection**

Safety glasses with side protection shield (EN 166)

**Hand protection**

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

permanent use of protective gloves.

Appropriate Material butyl rubber

Material thickness 0.5 mm

Breakthrough time > 240 min

**Other**

Normal chemical work clothing.

**Environmental exposure controls**

No data available.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>			
liquid			
<b>Form/Colour</b>			
liquid			
black			
<b>Odour</b>			
characteristic			
<b>pH value</b>			
Value	appr.	4	
<b>Boiling point / boiling range</b>			
Value	appr.	75	°C
Reference pressure		1013	hPa
<b>Melting point/freezing point</b>			
No data available			
<b>Decomposition temperature</b>			
No data available			
<b>Flash point</b>			
Value	appr.	18	°C
<b>Ignition temperature</b>			
No data available			
<b>Flammability</b>			
No data available			
<b>Lower explosion limit</b>			
No data available			
<b>Upper explosion limit</b>			
No data available			
<b>Vapour pressure</b>			
Value	<	110	kPa
Reference temperature		50	°C
<b>Relative vapour density</b>			
No data available			
<b>Relative density</b>			
No data available			
<b>Density</b>			
Value	appr.	0.928	g/cm <sup>3</sup>
Reference temperature		20	°C
<b>Solubility</b>			

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

No data available

**Partition coefficient n-octanol/water (log value)**

No data available

**Viscosity**

Value	appr.	12	sec
Reference temperature		20	°C
Type	Efflux time		
Method	DIN cup 4 mm		

**Solvent separation test**

Value	<	3	%
-------	---	---	---

**Particle characteristics**

No data available

**9.2 Other information**

**Other information**

The physical data is that of the main component/s.

**SECTION 10: Stability and reactivity**

**10.1 Reactivity**

No data available.

**10.2 Chemical stability**

No data available.

**10.3 Possibility of hazardous reactions**

No data available.

**10.4 Conditions to avoid**

Heat, naked flames and other ignition sources. Moisture.

**10.5 Incompatible materials**

Acids; Alkalis; Oxidizing agents

**10.6 Hazardous decomposition products**

Hydrogen

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		5660	mg/kg bodyweight
Species	rat		
Source	Manufacturer		

Acute dermal toxicity			
No	Substance name	CAS no.	EC no.
1	1-methoxy-2-propanol	107-98-2	203-539-1
LD50		9999.99	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		

**Acute inhalational toxicity**

No data available

**Skin corrosion/irritation**

No data available

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

<b>Serious eye damage/irritation</b>
--------------------------------------

No data available
-------------------

<b>Respiratory or skin sensitisation</b>
--

No data available
-------------------

<b>Germ cell mutagenicity</b>
-------------------------------

No data available
-------------------

<b>Reproduction toxicity</b>
------------------------------

No data available
-------------------

<b>Carcinogenicity</b>
------------------------

No data available
-------------------

<b>STOT - single exposure</b>
-------------------------------

No data available
-------------------

<b>STOT - repeated exposure</b>
---------------------------------

No data available
-------------------

<b>Aspiration hazard</b>
--------------------------

No data available
-------------------

<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>
---

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.
---

## 11.2 Information on other hazards

### Endocrine disrupting properties

No data available.

### Other information

No data available.

## SECTION 12: Ecological information

### 12.1 Toxicity

<b>Toxicity to fish (acute)</b>
---------------------------------

No data available
-------------------

<b>Toxicity to fish (chronic)</b>
-----------------------------------

No data available
-------------------

<b>Toxicity to Daphnia (acute)</b>
------------------------------------

No data available
-------------------

<b>Toxicity to Daphnia (chronic)</b>
--------------------------------------

No data available
-------------------

<b>Toxicity to algae (acute)</b>
----------------------------------

No data available
-------------------

<b>Toxicity to algae (chronic)</b>
------------------------------------

No data available
-------------------

<b>Bacteria toxicity</b>
--------------------------

No data available
-------------------

### 12.2 Persistence and degradability

No data available.

### 12.3 Bioaccumulative potential

No data available.

### 12.4 Mobility in soil

No data available.

**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

#### 12.5 Results of PBT and vPvB assessment

No data available.

#### 12.6 Endocrine disrupting properties

No data available.

#### 12.7 Other adverse effects

No data available.

#### 12.8 Other information

##### Other information

Do not discharge product unmonitored into the environment.

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

##### Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

##### Packaging

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

### SECTION 14: Transport information

#### 14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

#### 14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT RELATED MATERIAL
EmS	F-E, S-E
Label	3

#### 14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint related material
Label	3

#### 14.4 Other information

No data available.

#### 14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

#### 14.6 Special precautions for user

No data available.

#### 14.7 Maritime transport in bulk according to IMO instruments



**Trade name:** edding Permanent Marker Refill Ink T25, T100, T1000 (black) contained in: edding 800

**Current version :** 7.3.0, issued: 01.03.2021

**Replaced version:** 7.2.0, issued: 01.06.2016

**Region:** GB

Not relevant

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

#### **Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

#### **REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

#### **Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No 3, 40
--	----------

#### **Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

### 15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

#### **Sources of key data used to compile the data sheet:**

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

#### **Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H318	Causes serious eye damage.

#### **Creation of the safety data sheet**

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: umco@umco.de

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 17962